Pipe Cutter Guide*



TF1 Filters



TF1 Omega Filter	Length of pipe to be removed		
22 mm Slip Socket	75 mm (compression nuts on)		
28 mm Slip Socket	95 mm (compression nuts on)		
22 mm Valves	200 mm		
28 mm Valves	210 mm		

TF1 Omega Filter service clearance required

No specific requirement as the filter can be rotated on a live system to allow the magnet to be removed.



TF1 Sigma Filter	Length of pipe to be removed		
22 mm Slip Socket	85 mm (compression nuts on)		
22 mm Valves	200 mm		
28 mm Valves	210 mm		

TF1 Sigma Filter service clearance required

No specific requirement as the filter can be rotated on a live system to allow the magnet to be removed.



TF1 Compact Filter	Length of pipe to be removed	
22 mm Valves	200 mm	
28 mm Valves	210 mm	

TF1 Compact Filter service clearance required 100 mm



TF1 Total Filter	Length of pipe to be removed	
22 mm Valves	200 mm	
28 mm Valves	210 mm	

TF1 Total Filter service clearance required 150 mm

Scale Reducers



Whole house protection

Electrolytic Scale Reducer	22 mm Compression	15 mm Compression	15 mm Push Fit
Space Required	195 mm	195 mm	185 mm
Pipe Cut	Remove 153 mm	Remove 155 mm	135 mm



Single appliance protection

Magnetic Scale Reducer	22mm Compression	15mm Compression	15mm Push Fit
Space Required	195 mm	195 mm	185 mm
Pipe Cut	Remove 153 mm	Remove 155 mm	135 mm